

Allen-Bradley Service Manual

152H-F25FAD-37

1. Description

Solid-State Controller with Fusible Disconnect, IP65 (Type 4/12) enclosure, 25 A, 15 Hp @ 460V AC Controller Rating, and 230V AC, 3-phase, 50 and 60 Hz Input Line

2. Specifications

Specification	Value
Manufacturer	Allen Bradley
Category	Drives
Product	Line SMC-Flex
Part	Number 152H-F25FAD-37
Weight	100.00 lbs (45.36 kg)
Bulletin	Number Solid-State Controller with Fusible Disconnect
Enclosure	Type IP65 (Type 4/12)
Controller	Rating 25 A, 15 Hp @ 460V AC
Input	Line Voltage 230V AC, 3-phase, 50 and 60 Hz
Control	Voltage 120V AC
Rated	Voltage 230V AC
Control	Type Standard
Hp	Rating 2

3. Product Information

Solid-State Controller with Fusible Disconnect, IP65 (Type 4/12) enclosure, 25 A, 15 Hp @ 460V AC Controller Rating, and 230V AC, 3-phase, 50 and 60 Hz Input Line

Technical specifications for 152H-F25FAD-37

Manufacturer Allen Bradley

Category Drives

Product Line SMC-Flex

Part Number 152H-F25FAD-37

Weight 100.00 lbs (45.36 kg)

Bulletin Number Solid-State Controller with Fusible Disconnect

Enclosure Type IP65 (Type 4/12)

Controller Rating 25 A, 15 Hp @ 460V AC

Input Line Voltage 230V AC, 3-phase, 50 and 60 Hz

Control Voltage 120V AC

Rated Voltage 230V AC

Control Type Standard

Hp Rating 2

Description

The Allen-Bradley 152H-F25FAD-37 SMC-Flex is a Solid-State Controller with Fusible Disconnect that features an IP65 (Type 4/12) enclosure. This module has a controller rating of 25 A, 15 Hp @ 460V AC and a rated voltage of 230V AC. It has an input voltage of 230V AC, 3-phase, 50 and 60 Hz and a control voltage of 120V AC.

www.oilautotech.com