

Allen-Bradley 1756 Series Service Manual

1756-CN2RXT

1. Description

Mfr. Part Number:

2. Specifications

Specification	Value
Manufacturer	Rockwell Automation
Brand	Allen-Bradley
Part	Number/Catalog No. 1756-CN2RXT
Series	ControlLogix
Module	Type Interface Module
Voltage	5.1 Volts DC
Current	1.3 Amperes
Power	Dissipation 6.6 Watts
ControlNet	Rate of Communication 5 Mbps
Logix	Communication Connections 128
Max	Connections Supported 131
Max	Number of Nodes 99
Slot	Width 1
Location	Chassis (Any Slot)
Weight	0.64 lbs (0.293 kg)
UPC	10612598554833 Description
The	Allen-Bradley 1756-CN2RXT is a redundant media, ControlNet communication bridge module where controller-to-controller interlocking and I/O updates always take precedence over messaging and program uploads and downloads. It is part of the ControlNet Communication Module series and is ideal for applications that require the use of 128 ControlNet connections per communication module. A ControlLogix-XT model it can provide control in operating environments where temperatures range between -25 and 70 °C (-13 and 158 °F). The 1756-CN2RXT ControlNet Interface su

3. Product Information

Mfr. Part Number:

1756-CN2RXT

Manufacturer: Allen-Bradley / Rockwell Automation

Description: Allen-Bradley 1756-CN2RXT ControlLogix-XT ControlNet Redundant Bridge Module

Full Description: Allen-Bradley 1756-CN2RXT ControlLogix-XT ControlNet Dual Capacity Redundant Media Bridge Module (100 connections), for use in harsh and corrosive environments with a temperature ranges from -25...70 °C (-13...158 °F) The Allen-Bradley ControlLogix 1756-CN2RXT is an Interface Module with 5.1 Volts DC, 1.3 Amperes, 6.6 Watts, and 5 Mbps. Technical specifications for 1756-CN2RXT

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-CN2RXT

Series ControlLogix

Module Type Interface Module

Voltage 5.1 Volts DC

Current 1.3 Amperes

Power Dissipation 6.6 Watts

ControlNet Rate of Communication 5 Mbps

Logix Communication Connections 128

Max Connections Supported 131

Max Number of Nodes 99

Slot Width 1

Location Chassis (Any Slot)

Weight 0.64 lbs (0.293 kg)

UPC 10612598554833 Description

The Allen-Bradley 1756-CN2RXT is a redundant media, ControlNet communication bridge module where controller-to-controller interlocking and I/O updates always take precedence over messaging and program uploads and downloads. It is part of the ControlNet Communication Module series and is ideal for applications that require the use of 128 ControlNet connections per communication module. A ControlLogix-XT model it can provide control in operating environments where temperatures range between -25 and 70 °C (-13 and 158 °F). The 1756-CN2RXT ControlNet Interface supports a total of 99 nodes and 131 connections -128 standard Logix connections plus 3 reserved for redundant control. Because these are reserved, the 3 connections will always appear in use even when they are open. The module comes with a communication rate of 5 Mbps, current draws of 1300 mA at 5.1V DC, and of 3 mA at 24V DC. Its isolation voltage is 30V (continuous) with a basic insulation type. The 1756-CN2RXT Module features one USB 1.1 full speed (12 Mbps) port and two ControlNet BNC ports requiring the 1786-RG6 quad-shield RG6 coaxial cable. It can occupy any chassis-based slot and is compatible with the 1756-A4LXT, 1756-A5XT, 1756-A7XT, and the 1756-A7LXT ControlLogix Chassis.

Website: www.oilautotech.com | Email: sales@oilautotech.com