

Allen-Bradley 1756 Series Service Manual

1756-OV16E

1. Description

Allen Bradley ControlLogix Electronically Fused Sinking Output Module with 16-Point Electronically Fused Outputs Technical specifications for 1756-OV16E

2. Specifications

Specification	Value
Manufacturer	Rockwell Automation
Brand	Allen-Bradley
Part	Number/Catalog No. 1756-OV16E
Series	ControlLogix
Module	Type Electronically Fused Sinking Output Module
Outputs	16-Point Electronically Fused
Voltage	12-24 Volts DC Sink
Operating	Voltage Range 10-30 Volts DC
Maximum	Output Current Rating-Point 1 Amp at 60 Celsius
Maximum	Output Current Rating-Module 8 Amps at 60 Celsius
Power	Dissipation (Max) 6.72 Watts at 60 Celsius
Backplane	Current at 5 Volts 210 milliamps
Removeable	Terminal Block(s) 1756-TBNH, 1756-TBSH
Isolation	Voltage 50 Volts Continuous
Enclosure	None
UPC	10612598264367 Description
The	1756-OV16E ControlLogix Digital DC Output Module by Allen-Bradley is an output module in the ControlLogix Digital DC output module series with 16 sinking and electronically-fused outputs located in the chassis slot of the 1756 ControlLogix device. It has a pilot duty rating of 1A (DC-13/SR) and an operational voltage rating of 10-30V DC. The 1756-OV16E has a nominal signal delay time o

3. Product Information

Allen Bradley ControlLogix Electronically Fused Sinking Output Module with 16-Point Electronically Fused Outputs Technical specifications for 1756-OV16E

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-OV16E

Series ControlLogix

Module Type Electronically Fused Sinking Output Module

Outputs 16-Point Electronically Fused

Voltage 12-24 Volts DC Sink

Operating Voltage Range 10-30 Volts DC

Maximum Output Current Rating-Point 1 Amp at 60 Celsius

Maximum Output Current Rating-Module 8 Amps at 60 Celsius

Power Dissipation (Max) 6.72 Watts at 60 Celsius

Backplane Current at 5 Volts 210 milliamps

Removeable Terminal Block(s) 1756-TBNH, 1756-TBSH

Isolation Voltage 50 Volts Continuous

Enclosure None

UPC 10612598264367 Description

The 1756-OV16E ControlLogix Digital DC Output Module by Allen-Bradley is an output module in the ControlLogix Digital DC output module series with 16 sinking and electronically-fused outputs located in the chassis slot of the 1756 ControlLogix device. It has a pilot duty rating of 1A (DC-13/SR) and an operational voltage rating of 10-30V DC. The 1756-OV16E has a nominal signal delay time of 75µs for OFF to ON state and 360µs for ON to OFF state and it has 1ms maximum delay time for both OFF to ON and ON to OFF. It has backplane ratings of 2mA at 5.1V and 210mA at 24V and a total power of 1.12W. The maximum power dissipation across the 1756-OV16E's circuits is 6.72W and the maximum leakage current on each point is 1mA in the OFF state. It has a maximum voltage loss of 700mV DC at 1A. The 1756-OV16E has a maximum current of 1A on each output point and the aggregate current on the module is 8A at 60 °C. The lowest current load on each point is 2mA and it has a surge of 2A for 10ms per point recurring every 2s. The 1756-OV16E has an insulation voltage of 250V adopting basic insulation type routinely tested at 1350V AC for 2s between outputs-to-backplane and output group-to-group. It has an IEC designated T4 temperature code and a North America T4 temperature code and it comes in an open enclosure. The 1756-OV16E functions best at 0-60 °C at 5-95% non-condensing humidity.