

Allen-Bradley 1756 Series Service Manual

1756-PSCA2K

1. Description

Allen Bradley ControlLogix Chassis Adapter Module for Redundant Power Supply which is mounted left of chassis Technical specifications for 1756-PSCA2K

2. Specifications

Specification	Value
Manufacturer	Rockwell Automation
Brand	Allen-Bradley
Part	Number/Catalog No. 1756-PSCA2K
Series	ControlLogix
Module	Type Chassis Adapter Module for Redundant Power Supply
Weight	8.1 ounces (0.228 kilograms)
Dimensions	5.51 x 4.41 x 5.71 inches
Mounting	Chassis - Left
Operating	Temperature 32-140 Fahrenheit (0-60 Celsius)
Backplane	Current (24 Volts) 125 milliamps
Power	Dissipation (Max) 25.7 Watts at 30 Celsius, 21.3 Watts at 60 Celsius
Removeable	Terminal Blocks 3 RTBs, 1756-TBSH or 1756-TBNH
Operating	Temperature 32-140 Fahrenheit (0-60 Celsius)
Enclosure	None The 1756-PSCA2 is a Chassis Adapter Module for a redundant power supply. Manufactured by Allen Bradley under the ControlLogix series, this module comes with shipping weight of 8.1 ounces and shipping dimensions of 1.38 x 6 x 5.81 inches. It is mounted on left chassis and comes with 3 RTBs featuring a 1756-TBSH or a 1756-TBNH. The module can endure an operating temperature of 0 to 60 degrees Celsius while the recommended storage

3. Product Information

Allen Bradley ControlLogix Chassis Adapter Module for Redundant Power Supply which is mounted left of chassis Technical specifications for 1756-PSCA2K

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-PSCA2K

Series ControlLogix

Module Type Chassis Adapter Module for Redundant Power Supply

Weight 8.1 ounces (0.228 kilograms)

Dimensions 5.51 x 4.41 x 5.71 inches

Mounting Chassis - Left

Operating Temperature 32-140 Fahrenheit (0-60 Celsius)

Backplane Current (24 Volts) 125 milliamps

Power Dissipation (Max) 25.7 Watts at 30 Celsius, 21.3 Watts at 60 Celsius

Removeable Terminal Blocks 3 RTBs, 1756-TBSH or 1756-TBNH

Operating Temperature 32-140 Fahrenheit (0-60 Celsius)

Enclosure None The 1756-PSCA2 is a Chassis Adapter Module for a redundant power supply. Manufactured by Allen Bradley under the ControlLogix series, this module comes with shipping weight of 8.1 ounces and shipping dimensions of 1.38 x 6 x 5.81 inches. It is mounted on left chassis and comes with 3 RTBs featuring a 1756-TBSH or a 1756-TBNH. The module can endure an operating temperature of 0 to 60 degrees Celsius while the recommended storage temperature for the 1756-PSCA2 is -45 to 60 degrees Celsius. The module can be placed on either of the slots on the left side chassis. With a Backplane current of 125 Milliamps at 24 Volts, the 1756-PSCA2 has a maximum power Dissipation of 25.7 Watts at 30 degrees Celsius and at 60 degrees Celsius, the maximum power dissipation is 21.3 Watts. This module provides two redundant power supplies into a single power connector on the chassis backplane and it is also an essential component when it comes to building ControlLogix Redundant Power Supply Systems. Only one of them is required for creating a system and comes compatible with the bulletin 1756-PA75R and the 1756-PB75R power supplies. Being an open type device, the 1756-PSCA2 redundant power supply has a current capacity of 1.5 Amps at 1.2 Volts DC, has 4 Amps at 3.3 Volts DC, 15 Amps at 5.1 Volts DC and 2.8 Amps at 24 Volts DC. Basically, the module is usually mounted horizontally on the left chassis and the left side cable used to connect the 1756-CPR2 to power supply. This cable comes with a bend of 5 inches as the minimum clearance to route and connect parts.

□