

Allen-Bradley 1756 Series Service Manual

1756-TBNH

1. Description

Mfr. Part Number:

2. Specifications

Specification	Value
Manufacturer	Rockwell Automation
Brand	Allen-Bradley
Part	Number/Catalog No. 1756-TBNH
Series	ControlLogix
Module	Type Terminal Block
Clamp	Type Screw-Clamp
Pins	20-Pin Connection
Weight	0.3 pounds (0.1 kilograms)
Backplane	Current (5Volts) 1,200 milliamps
Backplane	Current (24 Volts) 2.5 milliamps
Power	Dissipation (Max) 6.19 Watts
Wire	Size 20 AWG
Dimensions	5.51 x 4.41 x 5.71 inches
Operating	Temperature 32-140 Fahrenheit (0-60 Celsius)
Enclosure	None
UPC	10612598171856 Description
The	Allen-Bradley 1756-TBNH is a Removable Terminal Block (RTB) for 1756 I/O modules. It is an I/O module accessory and must be ordered separately. The 1756-TBNH provides flexibility in interconnecting 1756 I/O modules and industrial plant wiring. It plugs into the front of the I/O module. The 1756-TBNH removable terminal block is a 20-position NEMA screw-clamp. It has a 1.36 Nm Screw torque and an 8-mm (5/16 in.) maximum Screwdriver width. It has dimensions of 5.51 x 4.41 x 5.71 in. and weighs 0.3 pounds

3. Product Information

Mfr. Part Number:

1756-TBNH

Manufacturer: Allen-Bradley / Rockwell Automation

Description: Allen-Bradley 1756-TBNH ControlLogix 20 Position NEMA Screw Clamp Block

Full Description: Allen-Bradley 1756-TBNH ControlLogix 20 Position NEMA Screw Clamp Removable Terminal Block (RTB) The 1756-TBNH module is a removable terminal block or RTB module. It is manufactured in the ControlLogix series by Allen-Bradley/Rockwell Automation. The wires that are connected to the 1756-TBNH removable terminal block should all be the same size and they should either be all solid wires or all stranded wires because a mix of solid and stranded wires is not supported by the block. This Technical specifications for 1756-TBNH

Manufacturer Rockwell Automation

Brand Allen-Bradley

Part Number/Catalog No. 1756-TBNH

Series ControlLogix

Module Type Terminal Block

Clamp Type Screw-Clamp

Pins 20-Pin Connection

Weight 0.3 pounds (0.1 kilograms)

Backplane Current (5Volts) 1,200 milliamps

Backplane Current (24 Volts) 2.5 milliamps

Power Dissipation (Max) 6.19 Watts

Wire Size 20 AWG

Dimensions 5.51 x 4.41 x 5.71 inches

Operating Temperature 32-140 Fahrenheit (0-60 Celsius)

Enclosure None

UPC 10612598171856 Description

The Allen-Bradley 1756-TBNH is a Removable Terminal Block (RTB) for 1756 I/O modules. It is an I/O module accessory and must be ordered separately. The 1756-TBNH provides flexibility in interconnecting 1756 I/O modules and industrial plant wiring. It plugs into the front of the I/O module. The 1756-TBNH removable terminal block is a 20-position NEMA screw-clamp. It has a 1.36 Nm Screw torque and an 8-mm (5/16 in.) maximum Screwdriver width. It has dimensions of 5.51 x 4.41 x 5.71 in. and weighs 0.3 pounds. For wiring, use 0.33 - 2.1 mm² (22 - 14 AWG) solid or stranded copper wire rated at 90 °C (194 °F) or greater with a 1.2-mm (3/64-in.) gauge maximum insulation must be used. On any single terminal, do not wire more than two conductors. Every ControlLogix I/O module mounts on any ControlLogix chassis and requires a removable terminal block (RTB) to connect all the field-side wiring. Each I/O module has many applications ranging from high-speed digital processing to process control. In ControlLogix architecture, input and output status is shared among multiple controllers in the same or different chassis using producer-consumer technology. The 1756-TBNH RTB is intended for use in a clean and dry industrial environment with a 0-60 °C operating temperature and a 30g operating shock.

Website: www.oilautotech.com | Email: sales@oilautotech.com