

# IC693PBM200-DE

GE Fanuc / GE Intelligent Platforms (now Emerson) · Series 90-30

---

Series 90-30 PROFIBUS-DP master communications module, DE variant.

## Communication

**Protocol:** PROFIBUS DP-V0 Master

**Serial Service Port:** 1 RS-232 service port

**Profibus Port:** 1 Profibus master port (9-pin D-Sub, RS-485)

**Maximum DP Slaves:** 125

**Input Data Capacity:** 244 bytes

**Output Data Capacity:** 244 bytes

**Baud Rates:** 9.6K, 19.2K, 93.75K, 187.5K, 500K, 1.5M, 3M, 6M, 12M baud

## Electrical

**Backplane Current Consumption:** 450 mA typical at 5 VDC

## Environmental

**Operating temperature:** 0 to 60 °C

**Storage temperature:** -40 to +85°C

**Relative humidity:** 5 to 95% non-condensing

**Protection rating:** IP20

## Physical

**Dimensions (H×W×D):** 124 × 30 × 114 mm (single slot I/O module, supplier-reported)

**Weight:** 0.60 kg

## Lifecycle

**Lifecycle:** Legacy/obsolete in aftermarket listings; official Emerson EOS date not verified (Last verified: 2026-09)