

Schneider Series Service Manual

140ARI03010C

1. Description

The 140ARI03010C is an input module from Schneider Electric's Modicon Quantum series, designed specifically for handling analog input signals. It features a total of 8 analog inputs that are differential, with a resolution of 13 bits for accurate readings in real-time applications.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Line Modicon Quantum
Part	Number 140ARI03010C
EAN	3595860003430
Name	Input Module
Input	Type Analog
Number	of Analog Inputs 8
Analog	Input Type Differential
Input	Resolution 13-bit
Local	Signaling LEDs
Power	Dissipation 1W
Module	Format Standard
Altitude	5000 meters (16404 feet)
RoHS	Compliant Yes

3. Product Information

www.oilautotech.com

The 140ARI03010C is an input module from Schneider Electric's Modicon Quantum series, designed specifically for handling analog input signals. It features a total of 8 analog inputs that are differential, with a resolution of 13 bits for accurate readings in real-time applications.

Technical specifications for 140ARI03010C

Manufacturer Schneider Electric

Product Line Modicon Quantum

Part Number 140ARI03010C

EAN 3595860003430

Name Input Module

Input Type Analog

Number of Analog Inputs 8

Analog Input Type Differential

Input Resolution 13-bit

Local Signaling LEDs

Power Dissipation 1W

Module Format Standard

Altitude 5000 meters (16404 feet)

RoHS Compliant Yes

Description

Part of the Modicon Quantum series by Schneider Electric, the 140ARI03010C input module is designed for high-performance applications requiring analog signal processing. It accommodates 8 analog inputs, allowing for comprehensive data acquisition in various systems. The differential analog input type ensures enhanced accuracy, with a notable input resolution of 13 bits, yielding precise measurement capabilities.

Local signaling is provided via built-in LEDs that support easy monitoring of the module's status. This module operates with a low power dissipation of only 1 watt, maximizing energy efficiency in embedded systems. The standard module format makes it easy to integrate into existing frameworks, with dimensions of 1.97 by 6.5 by 12.2 inches (50 x 165 x 310 mm).

Weighing just 0.7 lbs (0.3 kg), this module is suitable for applications where weight is a consideration. It can function at significant altitudes, up to 5000 meters (16404 feet), and meets RoHS compliance for environmentally-conscious projects. The 140ARI03010C is an effective choice for automation tasks requiring reliable analog input handling and precise signal representation.

Range of Product

Modicon Quantum automation platform

Product or Component Type

Analogue input module

Complementary

Analogue input number

8

Input type

Differential

Addressing requirement

9 input words

Analogue input type

Temperature probe - 100...450 °C Pt 100, Pt 200, Pt 500, Pt 1000

Temperature probe - 200...850 °C Pt 100, Pt 200, Pt 500, Pt 1000

Temperature probe - 60...180 °C Ni 100, Ni 200, Ni 500, Ni 1000

Temperature probe 0.5 mA Ni 100, Ni 200, Ni 500, Ni 1000

Temperature probe 2.5 mA Pt 100, Pt 200, Ni 100, Ni 200

Analogue input resolution

13 bits

Input impedance

>= 10 MOhm

Absolute accuracy error

0.1 °C

Linearity error

+/- 0.01 % full scale

+/- 0.5 °C

Accuracy drift according to temperature

+/- 0.5 °C 77 °F (25 °C)

+/- 0.9 °C 32...140 °F (0...60 °C)

Isolation between channels and bus

1780 V AC 47...63 Hz 60 s

2500 V DC 60 s

www.oilautotech.com

Isolation between channels
300 Vrms AC
Update time
1200 ms 3 wires
640 ms 2 wires/4 wires
Fault type
Broken wire
Overtaking scale
Marking
CE
Local signalling
1 LED (green) for bus communication is present (Active)
1 LED (red) for external fault
8 LEDs (green) for channel is turned on
8 LEDs (red) for channel fault
Bus current requirement
200 mA
Power dissipation in W
1 W
Module format
Standard
Net Weight
0.7 lb(US) (0.3 kg)
Environment
Protective treatment
Conformal coating Humiseal 1A33
Standards
UL 508
CSA C22.2 No 142
Product Certifications
FM Class 1 Division 2
cUL
Resistance to electrostatic discharge
4 kV contact IEC 801-2
8 kV on air IEC 801-2
Resistance to electromagnetic fields
9.1 V/m (10 V/m) 80...1000 MHz IEC 801-3
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Relative Humidity
95 % without condensation
Operating altitude
<= 16404.2 ft (5000 m)
Ordering and shipping details
Category
US1PC2118155
Discount Schedule
PC21
GTIN
3595860003430
Returnability
No
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1

www.oilautotech.com

Package 1 Height
2.0 in (5.0 cm)
Package 1 Width
6.5 in (16.5 cm)
Package 1 Length
12.2 in (31.0 cm)
Package weight(Lbs)
16.3 oz (463.0 g)

www.oilautotech.com