

Schneider Series Service Manual

170INT11000C

1. Description

The 170INT11000C is an Interbus communication adaptor developed by Schneider Electric, part of the Modicon Momentum series. It enables connection with a high transmission rate of 500 kbit/s, supporting various devices in industrial systems.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type Interbus Communication Adaptor
Product	Line Modicon Momentum
Part	Number 170INT11000C
EAN	3595863798814
Transmission	Rate 500 kbit/s
Transmission	Support Medium Twisted Pair
Topology	Ring
Number	of Devices Per Segment 0 to 254
Max	Cable Distance Between Modules 12800 m
Fail	State Fail Safe
Protection	Class IP20
Resistance	to Electrostatic Discharge 8 kV
Resistance	to Electromagnetic Fields 10 V/m
Operating	Altitude 5000 m

3. Product Information

www.oilautotech.com

The 170INT11000C is an Interbus communication adaptor developed by Schneider Electric, part of the Modicon Momentum series. It enables connection with a high transmission rate of 500 kbit/s, supporting various devices in industrial systems.

Technical specifications for 170INT11000C

Manufacturer Schneider Electric

Product Type Interbus Communication Adaptor

Product Line Modicon Momentum

Part Number 170INT11000C

EAN 3595863798814

Transmission Rate 500 kbit/s

Transmission Support Medium Twisted Pair

Topology Ring

Number of Devices Per Segment 0 to 254

Max Cable Distance Between Modules 12800 m

Fail State Fail Safe

Protection Class IP20

Resistance to Electrostatic Discharge 8 kV

Resistance to Electromagnetic Fields 10 V/m

Operating Altitude 5000 m

Description

The Schneider Electric 170INT11000C serves as an Interbus communication adaptor within the Modicon Momentum range. This unit stands out with a notable transmission capability of 500 kbit/s over twisted pair cables. Connecting devices through a ring topology allows for a flexible network structure. A maximum of 254 devices can be connected per segment, making it suitable for extensive system architectures.

In the context of installation, the maximum cable distance between modules reaches an impressive 12,800 meters. This feature provides significant coverage for large-scale applications. The device operates in a fail-safe mode, increasing robustness by ensuring stable performance under adverse conditions. Weighing just 0.07 kg, it is lightweight yet designed with a protection class of IP20 to guard against solid particle ingress.

Moreover, the 170INT11000C is resilient to environmental stresses, demonstrating resistance to electrostatic discharges up to 8 kV and electromagnetic fields of 10 V/m. This ensures reliable operation in challenging electrical environments. Additionally, the unit can function effectively at altitudes of up to 5000 meters. This combination of performance and resilience makes it a reliable component for complex industrial communication infrastructures.

Range of Product

Modicon Momentum automation platform

Product or Component Type

Interbus communication adaptor

Complementary

Communication Port Protocol

Interbus generation SUP1 2

Transmission support medium

Twisted pair

Transmission Rate

500 kbit/s

Topology

Ring

Net Weight

0.15 lb(US) (0.07 kg)

Environment

IP Degree of Protection

IP20

Protective treatment

Conformal coating Humiseal 1A33

TC

Marking

CE

Ordering and shipping details

Category

US1PC3118206

Discount Schedule

PC31

GTIN

3595863798814

Returnability

www.oilautotech.com

No
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1
Package 1 Height
2.2 in (5.5 cm)
Package 1 Width
7.09 in (18.0 cm)
Package 1 Length
10.2 in (26.0 cm)
Package weight(Lbs)
6.8 oz (193.0 g)
Unit Type of Package 2
S02
Number of Units in Package 2
2
Package 2 Height
5.9 in (15.0 cm)
Package 2 Width
11.8 in (30.0 cm)
Package 2 Length
15.7 in (40.0 cm)
Package 2 Weight
13.6 oz (386.0 g)

www.oilautotech.com